



## **Aluzone Pure FSC parasol**

Tradewinds Aluzone parasols were designed to offer a modern lightweight yet strong parasol utilizing a modern mix of aluminium, stainless steel and the finest kiln dried Eucalyptus timber that is FSC (Forestry Stewardship Council) certified. High quality materials and workmanship ensure that Tradewinds parasols are the no 1 choice for corporate, private & promotional buyers.

Stainless steel fittings are used for high durability and fabric options are naturally resistant to rotting and mildew, acids and alkalis and in addition, all fabrics are Teflon treated to provide water, oil and soil protection.

### **Key Features:**

- Extruded aluminium frame 1.5mm wall thickness
- Strut section 25,5 x 19,76mm and 34,9 x 22.2mm
- Plastic end caps ABS Terpolymer
- Hub produced from laminated FSC certified Eucalyptus Diversicolor (karri)
- All fittings and fasteners produced from marine grade stainless steel 304
- U-bracket system for easy removal & replacement
- Stainless Steel Pulley system

The wood in Aluzone frames come from well managed forests independently certified in accordance with the rules of the Forest Stewardship Council. Certified by SGS Qualifor, certificate no. SGS-COC-003833. Manufactured in South Africa by Tradewinds Parasol (Pty) Ltd.

### **Opening the umbrella and Safety**

When opening the umbrella, pull out the ribs to ensure they move freely, and then gently pull on the pulley cord to slowly raise the sliding hub upwards. Continue to raise until the fabric is taut and then insert the pin into the highest possible hole. A tautly erected umbrella will be stronger and will not allow the canvas to whiplash in the wind which may cause the strut ends to break. The umbrella should be closed prior to the onset of strong gusty wind conditions and covered with heavy duty protective PVC cover only when dry.

### **Timber & Aluminium Maintenance**

The aluminium components of this umbrella may be cleaned with detergents such as Handy Andy. It is recommended that Natural Timber Sealer or similar high quality sealer or penetrating oil specified for outdoor applications be used for maintenance of the wooden hub.

### **Fabric Maintenance**

To clean the fabric, open the umbrella and put on its side and remove dirt using a soft brush with water. In order to protect the Teflon properties, use only a mild detergent that does not contain ammonia and never dry-clean the fabric.

### **Guarantee**

Aluzone parasols are guaranteed, from original date of purchase by the initial buyer, for a period of 2 years against defects in metal fixtures & fittings and against defects resulting from faulty workmanship. Although the manufacturer strives to provide the highest quality, we accept no responsibility for defects in timber, colour variation of processed wood, fading of fabric or fabric print degradation. The manufacturer will not be liable for any extra costs incurred by the buyer as a result of defects found in the product or as a result of faulty product, over and above those covered in the guarantee contained in the paragraph above.

Tradewinds products are covered by a full spares backup from our international dealer network.